



GENERAL CATALOGUE



- 01 **Saw Machines**
- 02 **Coring, Grinding, Cutting, Diamond Abrasives**
- 03 **Plumbing Machines & Tools**
- 04 **Plastic Welding Machines & Accessories**
- 05 **Compressors & Rebar Machines**
- 06 **Construction Materials**
- 07 **Building Materials**
- 08 **Building Materials & Gas Monitors**
- 09 **Lifting Equipments**
- 10 **Industrial Sockets & Cable Reels**
- 11 **Industrial Fans**
- 12 **Industrial Fans**
- 13 **Industrial Workwear**
- 14 **PPE Hand Protection**
- 15 **Spectacles & Helmets**
- 16 **Personal Protective Equipment**
- 17 **Hand Tools**

Contents



Floor Grinding / Floor Saw Machines



FGE 270



FSE 1274

Diamond Core Machines



Table Saw Machines



TME 700

Floor Saw / Ring Saw



HRE 400



HBE 350

Wall Saw / Cutoff Machines



WSE 811



Tyrocut MI400

Diamond Cup Wheels / Floor Grinding Tools



Coring Applications - Corebits



Diamond Saw Blades



Pre Cast & Wall Saw Blades



Pre Cast Blades upto 1300mm

Wall Saw Blades upto 1200mm

Colour Codes

Label



Steel



2in3/1in1



INOX



Nonferrous metals



Cast iron



Stone

Cutting Applications



Grinding Applications



Finishing Applications



Colour Codes

Label



Universal



Concrete



Hard stone



Tiles



Marble



Asphalt



Abrasive materials



Tools



Electric Threading



Pipe Grooving



Electric Test Pump



Manual Threading



Electro-Fusion Welding



PPR Socket Welding



Drain Cleaning Machine



Manual Test Pump



Pipe Hole Saw Machine



Manual Threading



Hydraulic Pipe Bender

Accessories



Threading Oil



Threading machine
Carrying Table




Pipe Threading Dies



Pipe Support Stand




Butt Fusion Welding Machines



Accessories



Pipe Roller



Air Compressors



EASY - Series



EASY - Series



EASY - Series: ECW 100/2M, 150/2M, 270/3M, 500C/7,5T, 500C/5, 5T

Air Compr(Ltr - Hp): 100ltr-2Hp, 150ltr-2Hp, 270ltr-3Hp, 500ltr-5,5Hp, 500ltr-7,5Hp



Rebar Machines



TECHNICAL FEATURES

- Increased cutting capacity
- IP54 motherboard
- 2 wheels
- Heavy duty Machines
- Gears in cemented steels

Cutting Capacity: 10 to 30mm



Screw Locator



Adjustable according to bar's diameter & bars' quantity to cut

5 pin plug



Easiest system to change the phase in case of wrong connections.

Construction Materials



POWER TROWEL

PLATE COMPACTOR



FLOOR SAW



PLATE COMPACTOR



VIBRATOR



TAMPING RAMMER


CONCRETE MIXER



HOSE



Heavy Duty Tarpaulin



Canvas Tarpaulin

Polypropylene Rope



Building Materials

G.I BINDING WIRE



Usage/Application:
Industrial

Black Annealed Binding Wires

High tensile strength, longer service life

Available Guage: 14, 16, 18, 20, 22



High tensile strength,
longer service life



Cotton Rags



KISWEL



made in Korea

Welding Consumables



Gypsum Boards



Gypsum Sheet
Regular



Gypsum Sheet
Fire Resistant



Gypsum Sheet
Moisture Resistant




PRIME GEOTEXTILE

Needle Punched
Nonwoven Geotextile
Products.



THERMAL INSULATION




Building Materials

DELCO
PLUS



FORTUNEPLY



FILM FACED PLYWOOD
(Full Hardwood)

Ordinary Plywood



Timber Wood



Jollyboard
LIMITED

**EXPANSION
JOINT FILLER
BOARDS**

For expansion joints
in concrete roofs,
slabs & vertical walls



**INJECTION PUMP &
STEEL PACKERS**



EMPRO

EMPRO PVC WS
JOINT SEALING PROFILES




Gas Detection

**INDUSTRIAL
SCIENTIFIC**



Gas Monitors



TANGO TX1
Single Gas Monitor
H₂S, CO, NO₂, SO₂

RATTLER T40
Single Gas Monitor
H₂S, CO

VENTIS MX4
Multi Gas Monitor
H₂S, CO, LEL, O₂, NO₂, SO₂

iBrid MX6
Multi Gas Monitor
H₂S, CO, LEL, O₂, NO₂, SO₂

RADUZ BZ1
Area Gas Monitor
H₂S, CO, LEL, O₂, NO₂, S

Lifting Equipment



ADJUSTABLE ALUMINIUM TRIPOD



Height adjustable from
1.20m to 1.97m
Breaking Strength:
2000 Kg



FULL BODY HARNESS LX495

FULL BODY HARNESS LX500

LANYARDS

NYLON SLING

POLYESTER LIFTING
WEBBING SLING
(Double ply)



CARGO LASHING BELT

Hydraulic Pallet Truck

Available Capacity in:
2.5 & 3.0 Ton



Chain Block



made in japan

VP-5 Series

Series

VP-5-05, 1/5T | VP-5-10, 1T | VP-5-15, 1.5T
VP-5-30, 3T | VP-5-50, 5T | VP-5-20, 2T
VL-5-90, 10T

VL-5 Series



10t

INDUSTRIAL SOCKETS & PLUGS



RR013
16A 3 Pin Plug 250v
(Male)



RR113
16A 3 Pin Wall
Mounted Socket 250v
(Female)



RR135MB
63A 5 Pin Socket 400v
(Female)



RR025
32A 5 Pin Plug 400v
(Male)

INSECT KILLER



RR-1K210 / 1K215
INSECT KILLER

Coverage Area:
60m / 80m

Plug Type:
1.2m BS plug



Cable Reel 4 Gang
50mtr Cable

Tower Socket 8s+
2usb



EXTENSION SOCKET
4G 3mtr
EB4NS1B

EXTENSION SOCKET
5G 3mtr
EB5NS1B



VINI
TAPE





Industrial fans

Axial fan

Portable Ventilator



Available Models:

PVT-20 to 50

Available Duct Hose:

5mtr / 10mtr



Available Inches:

8 inch, 10 inch, 12 inch, 14 inch,
16 inch, 18 inch, 20 inch

Floor Fan

FE Series Powerful Floor Fan



FE-30 Floor Fan

12" Inch



FE4-40 Floor Fan

16" Inch

Industrial fan



Deton Fans



DF Series Stand

Large air volume
Low noise
Aluminium Blade
220v / 50HZ



MFS-26L Stand Type

Effective area: 40-80m²
Water tank volume:
23 litres
Material: Metal



MFS-24/26 Stand Type

Effective area: 40-80m²
Water tank volume: 20 litres
Material: Metal

DF Series Wall Fan

Low noise
Aluminium Blade
220v / 50HZ



MFW-26L Wall Type

Effective area: 40-80m²
Spray distance: 8-10m
Material: Metal

Industrial Workwear

HIGH QUALITY SAFETY WORK WEAR



FABRIC SPECIFICATION:

235 GSM
100% Cotton
Breathable, Soft Finished
Shrinkage Below 2%



PROBAN

FIRE RETARDANT

FABRIC SPECIFICATION:

235 GSM
100% Cotton
Breathable, Soft Finished
Shrinkage Below 2%



FABRIC SPECIFICATION:

240 GSM
100% Cotton Mercerized
Pre-Shrunk Fabric
Fire Retardant
Shrinkage Below 2%



ALPHA SOLWAY

PROTECTIVE BOILERSUIT



**DISPOSABLE COVERALL
EN CAT 1**

Material:
PP Non-Woven
Weight: **50gsm**



**FR Cotton
Coverall**

EN11612, EN11611, EN14116,
EN1149

320 GSM / 260 GSM
Fire retardant
100%
Cotton



**Aluminized
Heat Protection
Jacket**



NOMADIC

A SHIELD OF SAFETY

FR **250 GSM**

**FLAME
RETARDANT
WINTER JACKET**



**Polyester Boiler Suit /
Cotton**

PPE & HAND PROTECTION

SKYTEC



OIL GRIP
IMPACT PROTECTION GLOVES
Cut level 1

CAT II EN 388:2016 EN407:2004
 CE 4142XP X2XXXX

OIL GRIP



CUT RESISTANT IMPACT GLOVES

CATIEN 388:2016ASTM / ANSI 105-2016
 CE 4X43DP A4 CUT ANSI / ISEA 138 2

Benchmark

CUT LEVEL D

SKYTEC



TP-5
 Polyurethane
 Coating **Cut level 5**

EN388: 2003 CAT II
 CE 4543

Globus GROUP



CHEMICAL RESISTANT GLOVES

BMG-560

EN ISO 374-1:CAT III 2016/Type A

A J K L M N O VIRUS CE 0120

SKYTEC

NEVADA™ Globus GROUP



CAT II EN 388:2016 EN 407:2004 ASTM/ANSI 1105-2016
 CE 2X41C X2XXXX A3 CUT

CUT RESISTANT SLEEVES

SKYTEC



CUT RESISTANT GLOVES

TONS TP-1 Cut level 1

EN 388: 2003 EN 388: 2016
 CE



N95 Face Mask

HIGH PROTECTION | BREATHABLE | ANTI MICROBIAL




SPARTAN SAFETY SPECTACLES & HELMETS

Lightweight and Comfortable

1

Hard Coat Clear Spectacles

Hard coating on lens
 Lens filters out **99.9%** of harmful UV light
 On-piece lens, with dual 10 base curvature



2

Hard Coat Anti Fog Spectacles


Hard coating on lens
 Lens filters out **99.9%** of harmful UV light
 Polycarbonate temple with polycarbonate lens



3


Hard Coat Dark Spectacles

Hard coating on lens
 Lens filters out **99.9%** of harmful UV light
 Polycarbonate temple with polycarbonate lens



SAFTEY HELMETS

Ultra 5000 Series

STANDARD:
 IS 2925:1984,
 EN 397, CE, DGMS Approved

- Resistant to high level impact
- Fully adjustable, Nylon ratchet for smooth & universal fit



Available Colors:



Built for Safety



S1P HRO

PUMA
643070



Safety Boots S3

PUMA
633140



S1P ESD HRO SRC

PUMA
643800



PUMA
644110

LOW CUT S1P



COMPOSITE



SLIP RESISTANT



BIG SIZES



WATERPROOF



Safety Boot
Apprentice



Safety Shoe
Cutter

Rubber Gum Boots




BATA INDUSTRIALS
THE SAFETY SHOE



Conquer
Oxford
High Cut



STORM
Safety Boot



STEEL TOECAP



OIL RESISTANT



ANTISLIP



SLIP RESISTANT



STEEL TOECAP



OIL RESISTANT



ANTISLIP



Measuring Tapes



Chisel Set



Socket Set



Cutting Saw



Spirit Levels



Hammers & Storage Boxes



Screw Drivers



Pliers, Cutters & Spanners



Folding and Hand Truck





SYNTHETIC ROPES LIKE POLYPROPYLENE ROPE (MOORING ROPES) NYLON ROPES , NYLON SLINGS , WEBBING SLINGS , ROUND SLINGS ETC.

NYLON / POLYESTER WEBBING SLINGS:

• According to Machinery Directive 2006/42/EC & EN 1492-1 • Safety Factor: 7:1 to EN 1492-1

Flat Eye Slings are the most common type of sling. They can be used in all three hitches – Vertical, Choker, and Basket. In addition to the color, the number of black lines on these slings indicates its WLL.

Type - Double ply polyester webbing sling with reinforced lifting eyes

ROUND SLINGS

Round slings are highly flexible, light weight and it is an all-purpose lifting sling enabling a strong and supportive for safe lifting of a load without any damage. Round slings are a continuous loop made from polyester yarn encased in a sleeve of polyester fabric.

Its Polyester characteristics support the lifting, with perfect surface contact in load and slings, Non damage of load surface, avoiding slippery and bouncing etc.



WORKING LOAD LIMIT (WLL) IN TONNE FOR ROUND SLINGS AND WEBBING SLING

SAFETY COLOUR CODE	Straight Lift	Choke Lift	Basket Lift	Mul ti Slings	
7-1 SAFETY FACTOR					
MODE	1.0	0.8	2.0	1.4	1.0
FACTOR	1 2	0.8	2 4	1.4	1 2
VIOLET	3	1.6	6	2.8	3
GREEN	4 5	2.4	8	4.2	4 5
YELLOW	6	3.2	10	5.6	6
GREY	8	4	12	7	8
RED	10	4.8	16	8.4	10
BROWN	12	6.4	20	11.2	12
BLUE	15	8	24	14	15
ORANGE	20	9.6	30	16.8	20
ORANGE	30	12	40	21	30
ORANGE		16	60	28	
ORANGE		24		42	



Mooring Rope (PP rope)



Manila Ropes



Nylon Ropes

ORANGE

GRADE 100 / 80 CHAIN & SLINGS

GRADE 100/ 80 LIFTING CHAIN AND SLINGS

Grade 100/ 80 Alloy steel chain is the most widely used chain for overhead lifting applications and is available from 9/32" through 1-1/2".

CHARACTERISTICS AND SPECIFICATION

Standard : EN 818 - 2
 Material : Alloy steel
 Factor of safety : 4 to 1
 Construction : Quenched & tempered
 Proof load : 2.5 times of working load limit

CHAIN SLINGS

Chain slings are available in a range of material grades, sizes and assemblies. Its mainly applicable in various types like Endless, Single leg , Double legs, Four Legs.

Its ends fittings are Clevis Type Hooks or D Shackles depends on the lifting plan and load requirements. Shortening Clutches are using for adjust the leg length if required.



GRADE 80 CHAIN SLING

Dia		1 Leg		2 Legs		3 & 4 Legs	
mm	inch	SWL vertical (t)	SWL choker (t)	SWL 0-45° Sling Angle to Vertical	SWL 0-30° Sling Angle to Vertical	SWL 0-45° Sling Angle to Vertical	SWL 0-30° Sling Angle to Vertical
7	9/32	1.5	1.2	2.12	2.60	3.18	3.90
8	5/16	2	1.6	2.83	3.46	4.24	5.20
10	3/8	3.15	2.52	4.45	5.46	6.68	8.18
13	1/2	5.3	4.24	7.50	9.18	11.24	13.77
16	5/8	8	6.4	11.31	13.86	16.97	20.78
20	3/4	12.5	10	17.68	21.65	26.52	32.48
22	7/8	15	12	21.21	25.98	31.82	38.97
26	1	21.2	16.96	29.98	36.72	44.97	55.08
32	1 1/4	31.5	25.2	44.55	54.56	66.82	81.84

TYPES OF STEEL WIRE ROPE SLINGS

WIRE ROPE SLING TYPES



Soft Eye Both End



Thimble Eye Both End



One End Soft Eye, Other End Thimble Eye



One end Soft Eye, other end Plain



One end Thimble Eye, other end Plain



Endless sling



4 Leg with end fittings



4 Leg with Soft Eye



2 Leg with Hooks



2 Leg with Soft Eye



Grommet Round Sling



Gator Laid Sling






Flat Braided Sling



Braided Sling

STEEL WIRE ROPE SLING

Dia		 Single Leg		 2 Legs SWL (0-45°)	 3 & 4 Legs SWL (0-45°)
mm	Inch	SWL Vertical (t)	SWL Choker (t)	Sling Angle To Vertical (t)	Sling Angle To Vertical (t)
6.8	1/4	0.5	0.4	0.7	1.0
10	5/16	0.813	0.6	1.1	1.7
13	3/8	2.133	1.04	1.8	2.7
16	1/2	4.6	1.68	2.9	4.4
19	5/8	6.2	2.64	4.6	6.9
22	3/4	8.6	3.68	6.4	9.7
26	7/8	10	4.96	8.7	13.0
28	1	13.1	6.88	12.0	18.0
32	1.1/8	16.6	8	14.0	21.0
36	1.1/4	18.5	10.48	18.3	27.5
38	1.3/8	24.8	12.56	23.2	34.8
44	1.1/2	34.7	14.8	25.9	38.9
52	1.3/4	40.1	20	34.7	52.0
56	2	54.2	27.76	48.6	72.9
64	2.1/4	76.5	32.08	56.1	84.2
76	2.1/2	103.3	43.36	75.9	113.8
89	3		61.2	107.1	160.0
	3.1/2		82.64	144.6	216.9

CHAIN & LEVER HOIST (ELECTRICAL & MANUAL)

Electric Chain Hoist



Manual Chain Hoist



Lever Hoist

Brands : Toho Japan , Toyo
Capacity: 0.75t , 1.5t , 3t and 6t
Chain length : 1.5 mtrs.



Trolley



Hand Winch



Pallet Lifter



Wire rope Puller

SHACKLES



D (Chain)



Bolt & Nut



Screw Pin



Wide Body



ROV

RIGGING ACCESSORIES AND END FITTINGS



Plate lifting Clamp
(Vertical)



Plate lifting Clamp
(Horizontal)



Pipe Lifting Hook



Beam Clamp



Wire Rope Clip



Master Link



Master Link Assembly



Thimble



Open Spelter Socket



Closed Spelter Socket



Shurloc Hook



Sling Hook



Wedge Socket



Snatch Block



Tail Board



Swivels



Load Binder



Turn



Eye Bolt



Hoist Ring



Container Hook





Resin

BELOW THE HOOK-MATERIAL HANDLING EQUIPMENT

Lifting Beams ,Spreaders and Frames Adjustable and Fixed

Versatile beam has adjustable spreaders and lifting bail standard to allow for handling of a wide range of loads with a single lifting beam. Product can be used with provided shackles or add optional hooks for increased versatility.



- Adjustable Bail
- Adjustable Spreads
- Better Stability
- Can handle both wide and unbalanced loads.
- Solution for low head room



Sack Lifting ring




Big Bag Lifting Frame



Man Basket



Lowering Belt Hook



Delta Plate



Pad Eyes



Rigging Rack

STEEL WIRE ROPE –SPOOLING & SOCKETING

On-Site Socketing



Sockets are the most efficient of wire rope terminations and if properly made will sustain the full breaking load of the rope. Traditionally the socketing material has been molten white metal or zinc. More recently, however, suitable synthetic resins have been developed.

On site socketing and customization of wire rope for

- Crane Ropes
- A&R Wires
- Winch Wires
- Mooring and Anchor
- Lines Tow and Work Wires



Wire rope Spooling and Replacing

We provide on site spooling services with 35Te – 150Te spooling machine with competent operator with highest standard of health and safety. Full technical and logistical support will be provided throughout the planning and operations .